

# Occhielli e forcelle

## PREISOLATI

Preisolati "easy entry"  
approvati din 46237

Temperatura di lavoro: 105°C Max

Contatto: Rame elettrolitico stagnato

Isolante: Nylon Easy Entry

Massima tensione: 300 Volt AC



	SEZIONE CAVO	CODICE	D2	B	L	F	E	D	DI	CONF.
Red	0,25 - 1.5mm <sup>2</sup> 22 - 16 AWG #	EPROC28000	2,7	6,0	20,0	6,0	11,0	4,1	1,6	1.000
		EPROC32000	3,2	6,0	20,0	6,0				
		EPROC37000	3,7	6,0	20,0	6,0				
		EPROC43000	4,3	8,0	22,0	7,0				
		EPROC53000	5,3	10,0	24,0	8,0				
		EPROC65000	6,5	11,0	26,5	10,0				
		EPROC84000	8,4	14,0	29,0	11,0				
EPROC10000	10,5	18,0	33,0	13,0						
Blue	1,50 - 2.5mm <sup>2</sup> 16 - 14 AWG #	EPBOC32000	3,2	6,0	20,0	6,0	11,0	4,5	2,3	
		EPBOC37000	3,7	6,0	20,0	6,0				
		EPBOC43000	4,3	8,0	22,0	7,0				
		EPBOC53000	5,3	10,0	25,0	9,0				
		EPBOC65000	6,5	11,0	27,5	11,0				
		EPBOC84000	8,4	14,0	30,0	12,0				
		EPBOC10000	10,5	18,0	33,0	13,0				
Yellow	4 - 6mm <sup>2</sup> 12 - 10 AWG#	EPGOC43000	4,3	8,0	25,0	8,0	13,0	6,5	3,6	
		EPGOC53000	5,3	10,0	27,0	9,0				
		EPGOC65000	6,5	11,0	28,5	10,0				
		EPGOC84000	8,4	14,0	33,0	13,0				
		EPGOC10000	10,5	18,0	37,0	15,0				
EPGOC13000	13,0	19,0	43,0	20,5						



	SEZIONE CAVO	CODICE	D2	B	L	F	E	D	DI	CONF.
Red	0,25 - 1.5mm <sup>2</sup> 22 - 16 AWG #	EPRFO32000	3,2	5,8	22,0	6,3	11,0	4,1	1,7	1.000
		EPRFO37000	3,7	5,8	22,0	6,3				
		EPRFO43000	4,3	6,4	21,6	6,3				
		EPRFO53000	5,3	9,5	22,0	7,0				
		EPRFO65000	2,5	12,0	28,2	11,0				
Blue	1,50 - 2.5mm <sup>2</sup> 16 - 14 AWG #	EPRFO84000	8,4	12,0	8,2	11,0	11,0	4,5	2,3	
		EPBFO32000	3,2	5,8	22,0	6,3				
		EPBFO37000	3,7	6,4	22,0	6,3				
		EPBFO43000	4,3	6,4	22,0	6,3				
		EPBFO53000	5,3	9,5	23,0	7,3				
Yellow	4 - 6mm <sup>2</sup> 12 - 10 AWG#	EPBFO65000	6,5	12,0	28,2	11,0	13,0	6,5	3,4	
		EPBFO84000	8,4	12,0	28,2	11,0				
		EPGFO37000	3,7	7,2	25,7	7,5				
		EPGFO43000	4,3	8,5	25,7	7,5				
		EPGFO53000	5,3	9,5	25,7	7,5				
EPGFO65000	6,5	12,0	31,7	12,0						
EPGFO84000	8,4	13,5	30,5	10,5						



# Occhielli - Forcelle

**NON ISOLATI**

**Occhielli - Forcelle non isolati**



**MATERIALE: RAME ELETTROSTAGNATO**

SEZIONE FILO AWG / mm <sup>2</sup>	CODICE	D2	B	L	F	E	D	DI
22 – 16AWG 0.5 – 1.5	ENOC250100	2.7	6.0	14.0	6.0	5.0	3.5	1.6
	ENOC300100	3.2	6.0	14.0	6.0			
	ENOC350100	3.7	6.0	14.0	6.0			
	ENOC400100	4.3	8.0	16.0	7.0			
	ENOC500100	5.3	10.0	18.0	8.0			
	ENOC600100	6.5	11.0	20.5	10.0			
	ENOC800100	8.4	14.0	23.0	11.0			
16 – 14AWG 1.5 – 2.5	ENOC320200	3.2	6.0	14.0	6.0	5.0	4.1	2.3
	ENOC350200	3.7	6.0	14.0	6.0			
	ENOC400200	4.3	8.0	16.0	7.0			
	ENOC500200	5.3	10.0	19.0	9.0			
	ENOC600200	6.5	11.0	21.5	11.0			
	ENOC800200	8.4	14.0	24.0	12.0			
	ENOC100200	10.5	18.0	27.0	13.0			
12 – 10AWG 4 - 6	ENOC400300	4.3	8.0	18.0	8.0	6.0	5.8	3.6
	ENOC500300	5.3	10.0	20.0	9.0			
	ENOC600300	6.5	11.0	21.5	10.0			
	ENOC800300	8.4	14.0	26.0	13.0			
	ENOC100300	10.5	18.0	30.0	15.0			
	ENOC120300	13.0	19.0	36.0	20.5			



**MATERIALE: RAME ELETTROSTAGNATO**

SEZIONE FILO AWG / mm <sup>2</sup>	CODICE	D2	B	L	F	E	D	DI
22 – 16AWG 0.5 – 1.5	ENFO300100	3.2	5.8	16.0	6.3	5.0	3.4	1.7
	ENFO350100	3.7	5.8	16.0	6.3			
	ENFO400100	4.3	6.4	15.6	6.3			
	ENFO500100	5.3	9.5	16.0	7.0			
	ENFO600100	6.5	12.0	22.2	11.0			
16 – 14AWG 1.5 – 2.5	ENFO300200	3.2	5.8	16.0	6.3	5.0	4.1	2.3
	ENFO250200	3.7	5.8	16.0	6.3			
	ENFO400200	4.3	6.4	16.0	6.3			
	ENFO500200	5.3	9.5	17.0	7.3			
	ENFO600200	6.5	12.0	22.2	11.0			
12 – 10AWG 4 - 6	ENFO400300	4.3	8.5	18.7	7.5	6.0	5.6	3.4
	ENFO500300	5.3	9.5	18.7	7.5			
	ENFO600300	6.5	12.0	24.7	12.0			
	ENFO800300	8.4	13.5	23.5	10.5			